

Medium, Heavy & Super Heavy Duty Models

RANGE FEATURES for all Medium, Heavy & Super Heavy Duty Models

- Heavy gauge stainless steel body and cavity
- Dual magnetron top feeding microwave distribution ensures even cooking pattern
- 5 power levels for greater cooking versatility
- Easily removable air filter
- One piece dishwasher proof roof liner
- One touch +20 seconds button
- Pull to open door with large display window
- Stackable

Additional features on programmable touch control models

- 30 program facility - for regular menu items or self service vending
- x2 double quantity pad
- Multistage cooking
- Cycle counter - records how often each program is used
- Program lock - allows one-touch operation
- Clean air filter reminder
- Variable beep tone



+20 seconds button - adds extra time while microwave continues to cook



Clear digital displays on both programmable touch and manual control models

CM1319/1329 1300 watt Medium Duty



Two 1300 watt medium duty models are available, the CM1329 with programmable touch controls and the CM1319 with manual dial controls.

CM 1319



CM 1329



	MODEL	CM1319 Manual Controls	CM1329 Programmable Controls
	OVEN CAPACITY		26 litres (0.9 cu.ft)
POWER OUTPUT (Watts)		1300	1300
POWER LEVELS (Watts)	High	1300	1300
	Medium	910	910
	Low	650	650
	Defrost 1	260	260
	Defrost 2	130	130
PLUG SOCKET		13 amp	13 amp
POWER SOURCE		230V/50Hz	230V/50Hz
FREQUENCY		2,430 MHz	2,430 MHz
WEIGHT		32 kg	32 kg
NO OF PROGRAMMES		-	30
DIMENSIONS HxWxD (mm)		368 x 464 x 557(40*)	368 x 464 x 557(40*)
CAVITY DIMENSIONS HxWxD		190 x 370 x 370	190 x 370 x 370

*Handle dimension

CM1619/1629 1600 watt
Heavy Duty



Two 1600 watt heavy duty models are available, the CM1629 with programmable touch controls and the CM1619 with manual dial controls.

CM 1619



CM 1629



At a glance	MODEL	CM1619 Manual Controls	CM1629 Programmable Controls	
	OVEN CAPACITY	26 litres (0.9 cu.ft)	26 litres (0.9 cu.ft)	
	POWER OUTPUT (Watts)	1600	1600	
	POWER LEVELS (Watts)	High	1600	1600
		Medium	1120	1120
	Low	800	800	
	Defrost 1	320	320	
	Defrost 2	160	160	
	PLUG SOCKET	13 amp	13 amp	
	POWER SOURCE	230V/50Hz	230V/50Hz	
FREQUENCY	2,430 MHz	2,430 MHz		
WEIGHT	32 kg	32 kg		
NO OF PROGRAMMES	-	30		
DIMENSIONS HxWxD (mm)	368 x 464 x 557(40*)	368 x 464 x 557(40*)		
CAVITY DIMENSIONS HxWxD	190 x 370 x 370	190 x 370 x 370		

*Handle dimension

CM1919/1929 1850 watt
Super Heavy Duty



Two 1850 watt super heavy duty models are available, the CM1929 with programmable touch controls and the CM1919 with manual dial controls.

CM 1919



CM 1929



At a glance	MODEL	CM1919 Manual Controls	CM1929 Programmable Controls	
	OVEN CAPACITY	26 litres (0.9 cu.ft)	26 litres (0.9 cu.ft)	
	POWER OUTPUT (Watts)	1850	1850	
	POWER LEVELS (Watts)	High	1850	1850
		Medium	1295	1295
	Low	925	925	
	Defrost 1	320	320	
	Defrost 2	185	185	
	PLUG SOCKET	13 amp	13 amp	
	POWER SOURCE	230V/50Hz	230V/50Hz	
FREQUENCY	2,430 MHz	2,430 MHz		
WEIGHT	32 kg	32 kg		
NO OF PROGRAMMES	-	30		
DIMENSIONS HxWxD (mm)	368 x 464 x 557(40*)	368 x 464 x 557(40*)		
CAVITY DIMENSIONS HxWxD	190 x 370 x 370	190 x 370 x 370		

*Handle dimension



CM1059/1069 1100 watt Light Duty



Two entry level 1100 watt light duty models are available, the CM1059 with manual dial controls and the CM1069 with programmable touch controls.

FEATURES

- 5 power levels for greater cooking versatility
- Stainless steel body and cavity
- Pull to open door with large display window

Additional features on the CM1069 model

- 20 programmes
- 3 stage cooking
- Instant programme start
- x2 double quantity pad
- +30 seconds button
- Program list review
- Cycle counter - records how often each program is used



CM 1059



CM 1069

	MODEL	CM1059 Manual Controls	CM1069 Programmable Controls
	OVEN CAPACITY		26 litres (0.9 cu.ft)
POWER OUTPUT (Watts)		1100	1100
POWER LEVELS (Watts)	High	1100	1100
	Medium	770	770
	Low	550	550
	Defrost 1	330	330
	Defrost 2	110	110
PLUG SOCKET		13 amp	13 amp
POWER SOURCE		230V/50Hz	230V/50Hz
FREQUENCY		2,430 MHz	2,430 MHz
WEIGHT		17.5 kg	17.5 kg
NO OF PROGRAMMES		-	20
DIMENSIONS HxWxD (mm)		297 x 517 x 412(40*)	297 x 517 x 412(40*)
CAVITY DIMENSIONS HxWxD		225 x 336 x 349	225 x 336 x 349

*Handle dimension

